

SPINDLE CLEANING-LUBRICATING DEVICE

AS-200B

CORDLEES!! BATTERY POWERED!!

WITH OUTSTANDING FUNCTIONALITY-MORE POWERFUL, MORE PRODUCTIVE



INEXPENSIVE-THE BEST VALUE ON THE MARKET, IDEAL FOR THE SMALLEST MILL USE TO THE LARGEST PLANT.

RELIABILITY-ESPECIALLY DESIGNED FOR MAXIMUM PERFORMANCE AND PRACTICAL USEFULNESS.

COMPACTNESS-PERMITS EASY ACCESS TO ALL PARTS WHERE IN-PLANT SERVICE REQUIRES.

LIGHTWEIGHT-CAN BE UTILIZED RAPIDLY AND EFFECTIVELY WITH MINIMUM EFFORT.

OPERATION-IDENTICAL TO THE PREVIOUS MODEL AS-100, EASY-TO-USE AND EASY-TO-MAINTAIN.

FEATURES

- THE MOST ADVANCED ENGINEERED AND EFFICIENT SYSTEM AVAILABLE IN THE INDUSTRY.
- FREE FROM MESSY POWER SUPPLY CORD, INCREASED EFFICIENCY AND UNMATCHED FLEXIBILITY.
- INTERCHANGEABLE NOZZLE PROVIDES GREATEST ADAPTABILITY REQUIRED TO SUIT SPECIFIC REQUIREMENTS.
- SIMPLICITY OF OPERATION, RELIABILITY AND DEPENDABILITY WILL INCREASE PRODUCTION AND EFFECTIVELY REDUCE YOUR OVERHEAD.

CLEANING 1. A CIRCULATORY CLEANING SYSTEM, EXTRACTING FILTHY OIL AND RETURNING PURIFIED OIL INTO THE BOLSTER ARE ACCOMPLISHED SIMULTANEOUSLY BY THE USE OF LUBRICATING GUN HOUSED WITH TWIN HEAD NOZZLE.

2. SIMPLE OPERATION. JUST REMOVE THE RUNNING PARTS AND INSERT THE LUBRICATING GUN INTO THE BOLSTER, SQUEEZE THE TRIGGER, IN A MATTER OF SECONDS CLEANING PROCESS WILL BE OVER.

3. SELECTIONS OF INTERCHANGEABLE TWIN HEAD NOZZLE MAKES IT FULLY FLEXIBLE AND ADAPTABLE IN SERVING VARIOUS MACHINE MODELS WITH DIFFERENT SIZES OF SPINDLES, ANOTHER KINDS OF PARTS.

LUBRICATION 1. OIL LEVEL CAN BE POSITIVELY CONTROLLED TO A FIXED VOLUME BY SIMPLY SETTING THE ADJUSTABLE TWIN HEAD NOZZLE TO THE REQUIRED HEIGHT.

2. ONCE THE NOZZLE HEIGHT IS SET, REGARDLESS OF THE VOLUME OF OIL REMAIN IN THE BOLSTER, OIL CAN BE REPLENISHED TO THE EXACT VOLUME AS SET.

3. TWIN HEAD NOZZLE PREVENTS ANY OVERFLOW SPILL AND EXCESSIVE OR INSUFFICIENT LUBRICATION.

OIL TANK CAPACITY	RINSING	10lit	POWER SUPPLY	DC 12 VOLT 36A
	LUBRICATION	10lit		
FILTER		WIRE GAUZE	GUN & NOZZLE	SELECTABLE TO ORDER
			WEIGHT	50kg
PUMP CAPACITY	RINSING	5kg/cm/1500rpm	DIMENSIONS	600mm(W)×280mm(D)×580mm(H)
	LUBRICATION	5kg/cm/1500rpm		



Head Office/3-1, Ichi-ban 3-Chome, Atsuta-ku, Nagoya 〒456
 TEL(052)671-5191~5 FAX(052)671-5196
 Office/Shizuoka, Toyama, Kantoh

Agents